

RJ45
RIGHT ANGLE JACK

IDC
Krone 45°–110 Dual

SCALE 1/4



Specification :

Material :
1. Panel : SPCC, 1.3 mm thickness with black color painted.
2. RJ45 Jack Housing : PBT, UL 94V–0.
3. RJ45 Jack contact material & finished :
   3–1. Phosphor Bronze with 50–60 micro–inch Nickel plated.
   3–2. Contact area : Min. 3mm 50 micro–inch Gold plated.
4. IDC Housing : PC, UL 94V–2, KRONE dual.
5. IDC Terminal material & finished :
   5–1. Phosphor Bronze with 50 micro–inch Tin–Lead plating over 50–60 micro–inch Nickel plated.
   5–2. 110 & Krone tool compatible.
   5–3. Use for 22–26 AWG stranded & solid wire.

Performance :
a. The IDC color codes combine two wirings of T568A & T568B.
b. Insertion force : 900 gms for 8 contacts.
c. Retention strength : 7.7 kgs between Jack and Plug.
d. Operation temperature : –40°C to 80°C.
e. Durability :
   e–1. Jack : 750 cycles Plug–Jack mating and unmating test, insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
   e–2. IDC : Max. 200 punching times.
f. The Cat.6 performance is in compliance with the ANSI/TIA/EIA 568 B.2–1 standard.

GENERAL TOLERANCE OF DIMENSIONS	
X.XXX	±0.005
X.XX	±0.05
X.X	±0.1

equip®

Cat.6 Patch Panel 24 Port UTP, 90° Type, Krone 45° - 110 Dual IDC, 1U, black